

GLA M700 and M750 Veterinary Thermometer		
Features	M700	M750
Temperatures In 8 To 15 Seconds	◆	◆
Accurate To Within 0.1°	◆	◆
Fahrenheit and Celsius Capability	◆	◆
Temperature Range F° / 34° to 150°		
Temperature Range F° / 25° to 170°	◆	◆
Temperature Range C° / 0° to 60°		
Temperature Range C° / -3° to 65°	◆	◆
Peak Temperature Hold - Displayed On Screen	◆	◆
Audible Peak Temperature Indicator	◆	◆
Fast & Continual Charging	◆	◆
Charging Indicator - Actual Battery Voltage	◆	◆
Charging Indicator	◆	◆
Low Battery Warning	◆	◆
Audible Low Battery Warning	◆	◆
Audible Tones (On/Off) Determined By Customer		◆
Automatic Shut-Off After 5 Minutes	◆	◆
Automatic Shut-Off Time Delay Determined By Customer		◆
Red LED Display With Ambient Light Adjustment	◆	◆
Operation Modes Displayed On LED	◆	◆
Initial Display Information Screen	◆	◆
Self Re-Setting Fuse	◆	◆
Calibration Check Position	◆	◆
Interchangeable With All GLA Probes	◆	◆
Microprocessor Controlled	◆	◆
Damaged Probe Warning Display	◆	◆
25 Memory Locations		
253 Temperature And ID Storage Locations		◆
RS232 Port Output Connector And Cable		◆
1200 Modem Baud Rate		
9600 Modem Baud Rate Supplied with Null Modem Cable		◆
RFID Reader Compatible		◆
Real Time Clock Feature		◆
Audible Indicator Of Temperature Storage		◆
Audible Indicator Of ID Storage		◆
Information Can Be Downloaded Into Spreadsheets		◆
Last Four Digits Of Tag Displayed On LED		◆
Manual Entry of ID Through Computer Interface		◆
Thermometer Comes With M207 Probe & C725 Charger	◆	◆
Two Year Warranty	◆	◆
Made In USA By GLA	◆	◆
Machined Aluminum With A Powdercoat Finish	◆	◆
Machined Aluminum Inner Support Rails	◆	◆
Size: 3x1.75x5 inches (7.6x4x12.7cm)	◆	◆
Weight: 22 oz (617gm)	◆	◆